



TC-C32KN Spec:I3/E/Y/2.8mm/V4.1

2MP Fixed IR Dome Camera

Lite Series



KEY FEATURES

- Metal+Plastic Housing
- Up to 1920x1080@30fps
- S+265/H.265/H.264
- Min. illumination Color: 0.02Lux@F2.0
- Smart IR, IR Range: 30m
- Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -35°C~60°C, 0~95% RH
- POE,DC12V
- IP66, IK10



Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com
Website: en.tiandy.com

Tel: +86-22-58596065
Fax: +86-22-58596048



SPECIFICATIONS

Camera	
Image Sensor	1/2.8"
Signal System	PAL/NTSC
Min. Illumination	Color:0.02Lux@(F2.0,AGC ON),B/W:0Lux with IR
Shutter Time	1s to 1/100,000s
Day&Night	Dual IR Cut Filter with Auto Switch
WDR	DWDR
Lens	
Lens Type	Fixed
Focal Length	2.8mm
Lens Mount	M12
Aperture Range	F2.0,Fixed
Field of View	Horizontal field of view:99.7°; Vertical field of view:55.1°
Illuminator	
IR LEDs	8
IR Distance	Up to 30m
Wavelength	850nm
White LEDs	N/A
Compression Standard	
Video Compression	S+ 265/H.264B/H.264M/H.264H
Video Bit Rate	32kpbs~6Mpbs
Audio Compression	G.711A/G.711U/ADPCM_D
Audio Sampling Rate	8kHz/32kHz/48kHz
Image	
Max. Resolution	1920x1080
Main Stream	PAL:25fps(1920x1080,1280x720,704x576,640x480)
	NTSC:30fps (1920x1080,1280x720,704x480, 640x480)
Sub Stream	PAL:25fps(704x576,704x288,640x360,352x288)
	NTSC:30fps(704x480,704x240,640x360,352x240)
Third Stream	N/A
Image Setting	Saturation,brightness,contrast,sharpness,adjustable by client software or web browser
Image Enhancement	HLC/BLC/AGC/3D DNR
ROI	Yes,8 regions
OSD	16*16/32*32/48*48,adaptable size,Letters Such as Week,Date,Time,Total 1 Regions
Picture Overlay	N/A
Privacy Mask	Yes,4 regions
Defog	Yes

Tiandy

Feature	
Alarm Trigger	Disk Full,Disk R/W Error,IP Address Conflict,Mask Alarm
Video Analytics	Tripwire,Perimeter
Network	
ANR	Yes
Protocols	HTTP ,TCP/IP ,ICMP ,FTP ,DHCP ,DNS ,DDNS ,RTP ,RTSP,RTCP,NTP ,UPnP,UDP,HTTPS,QoS
System Compatibility	onvif Profile S/T/G,CGI,MILSTONE,RTMP
Remote Connection	2
Client	Easy7,EasyLive Plus
Web	N/A
Interface	
Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Audio I/O	N/A
Alarm I/O	N/A
Built-In Mic	N/A
Built-In Speaker	Yes
Reset Button	Yes
On-board storage	Built-in TF card slot,up to 512 GB
General	
Web Client Language	18 languages English,Russian,Spanish,Korean,Italian,Turkish,Simple Chinese,Traditional Chinese,Thai,French,Polish,Dutch,Hebrew,Arabic,Vietnamese,German,Ukrainian,Portuguese
Operating Conditions	-35°C~60°C,0~95%RH
Power Supply	DC12V, PoE (802.3af)
Power Consumption	8W
Protection	IP66


* Listed resolutions are only selectable options. It does not mean that all streams can work at their maximum resolution at the same time.



AVAILABLE MODEL

TC-C32KN Spec:I3/E/Y/2.8mm/V4.1

DIMENSIONS



ACCESSORIES



A36
Pole Mount



A35
Corner Mount



811
Junction Box



A29
Wall Mount



A25
Corner/Pole Mount



A20
Pendant Mount

DISTRIBUTED BY



Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com
Website: en.tiandy.com

Tel: +86-22-58596065
Fax: +86-22-58596048