

RG-EW1800GX PRO 1800M Wi-Fi 6 Dual-band Gigabit Mesh Router


DATASHEET



Highlights


- An Unprecedented Wireless Experience with Wi-Fi 6
- Strong Signal Received, Feels like "wall-less"
- Born For Multi-user, support up to 192 terminals
- Exclusive Reyee Mesh provides full space coverage Wi-Fi solution
- Take control of your home network at your fingertips

/ Highlight Features






Highlight Features





Highlight Features





.

	Basic
Dimensions (W×D×H)	180 mm x 180 mm x 30 mm (7.09 in. × 7.09 in. × 1.18 in. antennas not included)
Weight	0.55 kg (packages not included)
Wi-Fi Standards	Wi-Fi 6 (802.11ax)
MIMO	2.4 GHz, 2×2, MU-MIMO 5 GHz, 2×2, MU-MIMO
Max. Wi-Fi Speed	2.4 GHz: 574 Mbps 5 GHz: 1201 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80 MHz
Antennas	4
Antennas Type	External Omnidirectional
Antenna Gain	2.4 GHz: 5 dBi 5 GHz: 6 dBi
WAN Port	1×10/100/1000 Base-T Port
LAN Ports	4×10/100/1000 Base-T Ports
Recommended Users	48
Max. Users	192
Power Supply	DC 12V/1.5A
Power Consumption	≤18W
Operation Frequency Bands	802.11b/g/n/ax: 2.400 GHz to 2.483 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz 802.11a/n/ac/ax: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply
DFS	✓
Transmit Power	Regular: CE EIRP: ≤20 dBm (2.4 GHz) ≤27 dBm (5 GHz)
Operating Temperature	0 °C to +45 °C (32 °F to 113 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE,RoHS

	Wireless
OFDMA	✓
MU-MIMO	✓
BSS Coloring	✓
Maximum Number of SSIDs	6
SSID Hiding	✓
Band Steering	~
Guest Wi-Fi	✓
WPA/WPA2	✓
WPA3	✓ (only supported in ReyeeOS 1.219 and later versions)
Roaming	Layer 2 Roaming
Blacklist	✓
Reyee Mesh	✓
Mesh Pairing by Hardware	✓
Mesh Pairing by Mesh Button	✓
Mesh Pairing by Eweb	✓
Recommended Hop Count	≤5
Wi-Fi Optimization	✓
QoS (WMM)	✓
WPS	-
Transmission Power Adjustment	✓
Hardware Control of the Control of t	
CPU	MT7621
Flash	16M



Hardware Control of the Control of t		
RAM/SDRAM	256M	
Color	White	
System LED Indicator	✓	
Reyee Mesh LED Indicator	✓	
Reyee Mesh Button	✓	
Power Button	-	
Reset Button	✓	
DC Connector Dimensions	5.5 mm x 2.1 mm x 9.5 mm (0.22 in. \times 0.08 in. \times 0.37 in. antennas not included)	
	WAN	
Static IP	✓	
DHCP	✓	
PPPoE	✓	
Learning PPPoE Account & Password	✓	
VLAN Tagging	✓	
	LAN	
DHCP Server	✓	
Client List	✓	
Static IP Assignment	✓	
Port-Based Flow Control	✓	
Features		
TR069	✓	
IPv6	✓	
DDNS	✓	

Features		
IPTV	~	
Alarm	✓	
Diagnosis	✓	
UPnP	✓	
ARP Binding	✓	
Port Mapping	✓	
DMZ Host	✓	
Rate Limitation of Terminals	✓	
Hardware Acceleration	✓	
MAC Address Cloning	✓	
Cloud Management	✓	
Repeater Mode	✓	
WISP Mode	~	
	Security	
PPTP VPN Server	✓	
PPTP VPN Client	✓	
L2TP VPN Client	-	
Parental Control	✓	
Protect TCP Flood Attacks	✓	
Protect ICMP Attacks	~	
Protect UDP Flood Attacks	✓	
System		
Default Access/Password	192.168.110.1 No Password Required by Default	

System	
URL Access	✓
Local Upgrade	~
Online Upgrade	✓
APP Upgrade	~
Syslog	-
Backup	~
Factory Reset	✓
Language	Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian

Package Contents

Model	RG-EW1800GX PRO
Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Cat5e UTP Cable	1





Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd.
Website: https://reyee.ruijie.com/en-global