

RG-EW3200GX PRO 3200Mbps Dual-band Wi-Fi 6 Mesh Route

DATASHEET



Highlights

- Next-Gen Gigabit Wi-Fi 6 Standard
- 4x4 Enterprise-level Chipset, better stability under heavy load
- 8 Antennas and 8 Signal Amplifiers, provide whole-home network coverage
- Exclusive Reyee Mesh solution, one click to mesh up multiple Reyee Mesh devices
- Take control of your home network at your fingertips

/ Specifications

Basic Basic		
Dimensions (W×D×H)	190 mm × 190 mm × 41 mm (7.48 in. × 7.48 in. × 1.61 in. antennas not included)	
Weight	0.8 kg (packages not included)	
Wi-Fi Standards	Wi-Fi 6 (802.11ax)	
MIMO	2.4 GHz, 4×4, MU-MIMO 5 GHz, 4×4, MU-MIMO	
Max. Wi-Fi Speed	2.4 GHz: 800Mbps 5 GHz: 2402Mbps	
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80MHz	
Antennas	8	
Antennas Type	External Omnidirectional	
Antenna Gain	2.4 GHz: 5 dBi 5 GHz: 6 dBi	
WAN Port	1×10/100/1000 Base-T	
LAN Ports	4×10/100/1000 Base-T	
Recommended Users	60	
Max. Users	192	
Power Supply	DC 12V/2.5A	
Power Consumption	≤ 36 W	
Operation Frequency Bands	802.11b/g/n: 2.400 GHz to 2.483 GHz 802.11a/n/ac: 5.150 GHz to 5.350 GHz 802.11a/n/ac: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply	
DFS	Support	
Transmit Power	Regular: CE EIRP: ≤20 dBm (2.4 GHz) ≤27 dBm (5 GHz)	

Operating Temperature	-10 °C to +40 °C (14 °F to 104 °F)	
Operating Humidity	5% to 95% Noncondensing	
Certifications	CE	
Wireless		
OFDMA	Support	
MU-MIMO	Support	
BSS Coloring	Support	
Maximum Number of SSIDs	6	
SSID Hiding	Support	
Band Steering	Support	
Guest Wi-Fi	Support	
WPA/WPA2	Support	
WPA3	Support	
Roaming	Layer 2 Roaming	
Blacklist	Support	
Reyee Mesh	Support	
Mesh Pairing by Hardware	Support	
Mesh Pairing by Mesh Button	Support	
Mesh Pairing by Eweb	Support	
Recommended Hop Count	≤ 5	
Wi-Fi Optimization	Support	
QoS (WMM)	Support	
WPS	-	
Transmission Power Adjustment	Support	
Hardware		

СРИ	MT7622	
Flash	16 MB	
RAM/SDRAM	256 MB	
Color	Black	
System LED Indicator	Support	
Reyee Mesh LED Indicator	Support	
Reyee Mesh Button	Support	
Power Button	-	
Reset Button	Support	
DC Connector Dimensions	5.5 mm x 2.1 mm x 11.5 mm (0.22 in. × 0.08 in. × 0.45 in. antennas not included)	
WAN		
Static IP	Support	
DHCP	Support	
PPPoE	Support	
Learning PPPoE Account & Password	Support	
VLAN Tagging	Support	
	LAN	
DHCP Server	Support	
Client List	Support	
Static IP Assignment	Support	
Port-Based Flow Control	Support	
Features		
TR069	Support	
Preset	Support	
IPv6	Support	

DDNS	Support
IPTV	Support
Alarm	Support
Diagnosis	Support
UPnP	Support
ARP Binding	Support
Port Mapping	Support
DMZ Host	Support
Rate Limitation of Terminals	Support
Hardware Acceleration	Support
MAC Address Cloning	Support
Cloud Management	Support
Repeater Mode	Support
WISP Mode	Support
WISP Mode	Support Security
WISP Mode PPTP VPN Server	
	Security
PPTP VPN Server	Security Support
PPTP VPN Server PPTP VPN Client	Support Support
PPTP VPN Server PPTP VPN Client Open VPN Server	Support Support Support
PPTP VPN Server PPTP VPN Client Open VPN Server Open VPN Client	Support Support Support Support Support
PPTP VPN Server PPTP VPN Client Open VPN Server Open VPN Client L2TP VPN Client	Support Support Support Support -
PPTP VPN Server PPTP VPN Client Open VPN Server Open VPN Client L2TP VPN Client Parental Control	Support Support Support Support - Support
PPTP VPN Server PPTP VPN Client Open VPN Server Open VPN Client L2TP VPN Client Parental Control Protect TCP Flood Attacks	Support Support Support Support - Support Support Support - Support

Default Access/Password	192.168.110.1 No Password Required by Default
URL Access	Support
Local Upgrade	Support
Online Upgrade	Support
APP Upgrade	Support
Syslog	-
Backup	Support
Factory Reset	Support
Language	Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian

Package Contents

Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Cat5E UTP Cable	1





Copyright ©2000-2024 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd.
Website: https://reyee.ruijie.com/en-global